

# DRAF

## AKSİYEL FANLAR AXIAL FANS



- 765 m<sup>3</sup>/h – 3.700 m<sup>3</sup>/h hava debisi aralığında çalışmaktadır.
- Gövde DKP sacdan imal edilip korozyona karşı elektrostatik toz boya ile korunmuştur.
- Pervane galvaniz sacdan imal edilmiş olup dinamik balansı alınmıştır.
- Fanlarımızda dıştan rotorlu motor kullanılmıştır.
- Aspiratörlerimizin ön ve arka bölümlerinde muhafaza teli kullanılarak oluşabilecek tehlikeli durumlar engellenmiştir.
- Opsiyonel olarak hız kontrol cihazı ile hava debisi ve basınç ayarlanabilir.
- Yalıtım: Class B
- Koruma Sınıfı : IP 44

**Kullanım Alanları :** Bürolarda, ev ve işyerlerinde, çeşitli makine ve trafo soğutmalarında kullanıma uygundur.

- Has air flow between 765 m<sup>3</sup>/h and 3.700 m<sup>3</sup>/h.
- Casing and impeller are made of DKP sheet metal and protect against corrosion with electrostatic powder paint.
- Impeller made from galvanised sheet metal and dynamically balanced.
- Our axial fans are equipped with motors with external rotors.
- The possible danger is prevented by the protective wire mounted on the rear and front side of our fans.
- As an option, a speed control device can be used to adjust the air flow and pressure.
- Insulation : Class B
- Protection : IP 44

**Application Areas :** Suitable for use in housings and work place, for cooling of various machinery and substations.

### TEKNİK TABLO / TECHNICAL PARAMETERS

Tip Type	Voltaj Voltage V	Frekans Frequency Hz	Güç Power W	Akım Current A	Kondansatör Capacitor (µF/Volt)	Devir Speed d/d	Hava Debisi Air Flow m <sup>3</sup> /h	Ses Seviyesi Sound Pressure Level dB(A)	Ağırlık Weight Kg	Ambalaj Packing Adet
DRAF-200-2K-M	220	50	80	0,35	2,5/400	2700	765	59	2,30	1
DRAF-250-2K-M	220	50	110	0,49	2,5/400	2650	1750	69	2,90	1
DRAF-300-2K-M	220	50	170	0,78	4/400	2450	2350	70	3,60	1
DRAF-350-2K-M	220	50	260	1,10	6/400	2400	3700	75	4,35	1

Ses seviyesi 3m mesafeden ölçülmüştür. / Sound level has measured at a distance of 3 meters.

### TEKNİK ÇİZİM VE ÖLÇÜLER / TECHNICAL DRAWINGS AND DIMENSIONS

Tip / Type	A	B	C	D	E	F	G	H	I
DRAF-200-2K-M	265	200	185	80	75	5	5	84	30
DRAF-250-2K-M	325	258	235	90	85	5	5	94	30
DRAF-300-2K-M	400	310	285	95	88	7	5	99	35
DRAF-350-2K-M	440	360	335	100	93	7	5	104	40

Ölçümler mm cinsindedir. / Dimensions are in (mm)

